

EXG-FOPS FALLING OBJECT PROTECTIVE SYSTEM

* Attachments depicted may include optional upgrades or custom configurations.



This style of cab guarding is typically used in more extreme environments such as forestry, demolition, and quarry applications, as it provides full front and top cab coverage without attaching directly to the cab. The assembly is a one-piece fabricated HSS tube frame structure and includes a roof access hatch. It mounts to additional catwalks or a dedicated mounting kit, depending on machine configuration, and features one right rear leg vibration mount, front light mounts, and a cab access handle when the OEM handle must be replaced to maintain three-point contact for safety. The left rear leg is designed to maintain access to the cab filter.

Optional configurations can also include:

- Additional rubber mounts
- Left rear window guard
- Removeable Screen or Lexan glass with or in place of grid style front window protection.
- Roof access hatch opening trip system.
- Rear window Safe T Punch (must be used in order to meet B.C. WorkSafe guidelines for secondary escape).

Craig F.O.P.S guards are designed to meet and/or exceed the following safety codes:

- ISO 10262:1998 (Level II) & 3449:2005
- SAE Code J231 & J1356
- BC Work-Safe Code G602, G603 & G608

**Documentation is available for certified cab guarding upon request.*



Hartland Office
96 McLean Avenue
Hartland, NB
E7P 2K5 Canada

Ph: (506) 375-4493

Cambridge Office
315 Thompson Drive
Cambridge, ON
N1T 2B3 Canada

Ph: (519) 623-9500

Blackfalds Office
88 27323 TWP Rd 394
Lacombe County, AB
T4M 0S1 Canada

Ph: (403) 356-0048

Lawrenceburg Office
408 Commerce Way
Ethridge, TN
38456 USA

Ph: 1 (800) 867-1006

D.F.W. Office
6701 Snowden Rd
Fort Worth, TX
76140 USA

Ph: 1 (800) 867-1006



1-800-565-5007 • WWW.CRAIGATTACHMENTS.COM