

WL-HT HIGH TIP BUCKET

* Attachments depicted may include optional upgrades or custom configurations.



Increase the dump height of your wheel loader with a Craig High Tip Bucket. On most machines you can increase your dump height to exceed the OEM boom pin height allowing for applications such as loading high-side trucks without the need of a ramp.

- Dual cylinder design with cushion valve for smooth operation
- Visibility slots for accurate loading
- Flat bottom design allows easy penetration and loading
- Bucket hinge bushings are capped with metal clad wiper seals for extended life. Keeping grease in and debris out of critical pivot point on our high tip buckets
- Available in Craig Quik Key, OEM coupler and Pin-on configurations
- Critical wear areas utilize AR 400 wear plate
- Drilled to accept dealer specified edge, installed
- Optional third valve required on machine



Hartland Office
96 McLean Avenue
Hartland, IN
E7P 2K5 Canada

Ph: (506) 375-4493

Cambridge Office
315 Thompson Drive
Cambridge, ON
N1T 2B3 Canada

Ph: (519) 623-9500

Blackfalds Office
88 27323 TWP Rd 394
Lacombe County, AB
T4M 0S1 Canada

Ph: (403) 356-0048

Lawrenceburg Office
408 Commerce Way
Ethridge, TN
38456 USA

Ph: 1 (800) 867-1006

D.F.W. Office
6701 Snowden Rd
Fort Worth, TX
76140 USA

Ph: 1 (800) 867-1006



1-800-565-5007 • WWW.CRAIGATTACHMENTS.COM